

**3F** **Filippi**  
illuminazione

LED | 2018

**3F 66**

# 3F 66 LED



## Construction characteristics

### Illuminotechnical characteristics

Downward bilateral distribution.

Lifetime (L75/B10): 30000 h. (tq+25°C)

Lifetime (L70/B10): 50000 h. (tq+25°C)

Photobiological safety RG0 unlimited, risk absent, in compliance with IEC 62471, IEC/TR 62778.

### Mechanical characteristics

Self-extinguishing V2 polycarbonate housing, injection moulded, RAL 7035 grey.

Flow recuperator in specular aluminium with superficial titanium-magnesium treatment, non-iridescent.

Transparent PMMA diffuser, injection moulded, with smooth outer surface and differentiated prismatic inner surface.

Sealing gaskets between housing and diffuser in ecological anti-aging EPDM.

Diffuser safety seal with 4 latches attaching it to the housing, in stainless steel.

### Electrical characteristics

Electronic wiring 230V-50/60Hz, fuse.

In compliance with EN 60598-1.

Line entry at rear through rubber seal or at side after drilling.

## Source characteristics

- LED modules.
- Color initial tolerance (MacAdam): SDCM 4.

## On request


- LED sources with different colour temperatures
- different powers

## Applications

Wall mounting, particularly suitable for outdoor lighting of civil and industrial buildings, porticos, underpasses and walkways.


Controlled downward bilateral distribution provides uniform lighting on work surfaces. Control of light pollution, in accordance with the legislative requirements in force.

Dimensions



3F 66 LED

Code 8357



CE

650°C

IP65

Classe II

Driver/LED  
**SELV**

Assil  
Quality

Code	Item	Absorbed power (W)	Output flux (lm)	CCT (K)	CRI	Dimensions L x A x H
<b>Electronic</b>						
8357	3F 66 1 LED 6 II	10	665	4000	>80	255x176x344
8358	3F 66 2 LED 12 II	16	1302	4000	>80	255x176x344



To keep up to date on our initiatives and new products, subscribe to lightUpdate: news, events and new products directly in your email inbox. Information at the speed of Light.



Follow us on social media!

DP.0618.EN

**3F** **Filippi**  
illuminazione

**Web**  
**E-mail**  
**Telephone**  
**Fax**

[www.3F-Filippi.com](http://www.3F-Filippi.com)  
[export@3f-filippi.it](mailto:export@3f-filippi.it)  
+39 051 652 9611  
+39 051 775 884

**Head office and factory**

Via del Savena 28, Z.I. Piastrella  
40065 Pian di Macina, Pianoro (Bologna), Italy  
Tax Code. 01033260371 - VAT no. IT00529461204  
Share Capital € 3,000,000 fully paid up  
Bologna Register of Companies no. 01033260371  
REA (economic administrative index) No. 234613

**3F Filippi S.p.A.** is constantly striving to improve its products. Therefore, it reserves the right to modify the contents of this publication without prior notice.  
Check for any updates by visiting our website at [www.3F-Filippi.com](http://www.3F-Filippi.com), or contact our Sales Network.