




PRODUCT DETAILS



Dimensions



Accessories



AIRN T




AIRN T M SFD OPAL LED 8150lm/840
1x146W, FIX, RAL 9006

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: opal PMMA Housing: extruded aluminium Rope suspension 1,5 m (suspended version) Housing: grey RAL 9006 (G06)
SURFACE FINISH	220-240 V, 50-60 Hz
VOLTAGE	> 0,95
POWER FACTOR	8150 lm
NET LUMEN OUTPUT (Ta=25°C)	+/- 10 %
LUMINOUS FLUX TOLERANCE	146 W
POWER CONSUMPTION	56 lm/W
SYSTEM EFFICACY	4000 K
CORRELATED COLOUR TEMPERATURE	80 Ra
COLOUR RENDERING INDEX	3 SDCM
COLOUR TOLERANCE	A++ / A+ / A
EEC	I
PROTECTION CLASS	Passive
THERMAL MANAGEMENT	50,000 hours / L80 / B10
SERVICE LIFETIME (Ta=25°C)	From -20 °C to +35 °C
AMBIENT OPERATING TEMPERATURE	IP40
IP PROTECTION DEGREE	Diameter - 1206 mm, height - 111 mm
DIMENSIONS	13,6 kg
WEIGHT	

AREAS OF APPLICATION  **ARCHITECTURE AND MEDIA**
 **EDUCATION**
 **RETAIL AND PRESENTATION**



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.