



## PRODUCT DETAILS



## Dimensions



## Accessories



# ALASTAR Q

**ALASTAR Q M SFD OPAL LED 7700lm/840  
1x75W, FIX, RAL 9006**

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)


## Description

<b>MOUNTING</b>	Ceiling surfaced (SFD)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Opal diffuser (OPD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Diffuser: opal PMMA Housing: extruded aluminium Rope suspension 1,5 m (suspended version)
<b>SURFACE FINISH</b>	Housing: elox
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	7700 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	75 W
<b>SYSTEM EFFICACY</b>	103 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	I
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C
<b>IP PROTECTION DEGREE</b>	IP40
<b>DIMENSIONS (L x W x H)</b>	606 x 606 x 111 mm
<b>WEIGHT</b>	8,5 kg

## AREAS OF APPLICATION

- ARCHITECTURE AND MEDIA
- EDUCATION
- HOSPITALITY
- HOUSE AND FLAT
- RETAIL AND PRESENTATION

**LIDC**



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.