

Product: ARTSHAPE THREE LED MEDIUM EDGE ZAW TW 6000 PLX EDD 34 827-865 / Z-1,5M**Index:** OSTMPU60WTW7DZ

Description

Modernistic architectural luminaire in shapes of popular geometrical figures and fashionable design of simple form. The luminaire is adjusted to be mounted on the ceiling or suspended. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palette, the luminaires allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminaire is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

Product information

Category	Architectural luminaires
Family	ARTSHAPE THREE LED
Name	ARTSHAPE THREE LED MEDIUM EDGE ZAW TW 6000 PLX EDD 34 827-865 / Z-1,5M
Index	OSTMPU60WTW7DZ


Pictograms



Light and electrical data


Light source	LED
Luminous flux LED [lm]	5880
LED power [W]	51
Luminaire luminous flux [lm]	3057
Power of luminaire [W]	57
Luminaire's light efficiency [lm/W]	54
Color of the light [K]	2700 ÷ 6500
CRI	>80
SDCM (LED sources)	4
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)

Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,9
Dimensions [mm]	900 x 809 x 80÷90


A graph of light



Accessories


Index 6E1-500OKW1P-5

Name Suspension New Type-J 34 lenght
1,5m cable 5X 1-point



Index 6E1-8670-B-1,5

Name Suspension New Type-E lenght-
1,5 m without cable 1-point



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%.
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 26-05-2020