


Product: ARTSHAPE THREE LED LARGE FULL UP&DOWN 5000/16000 PLX E 34 840 / Z-1,5M

Index: 0STLPEUD50160APLXW9Z



Description

Modernistic architectural luminaire in shapes of popular geometrical figures and fashionable design of simple form. The luminaire is adjusted to be mounted on the ceiling or suspended. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palette, the luminaires allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminaire is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information

Category	Architectural luminaires
Family	ARTSHAPE THREE LED
Name	ARTSHAPE THREE LED LARGE FULL UP&DOWN 5000/16000 PLX E 34 840 / Z-1,5M
Index	0STLPEUD50160APLXW9Z
Pictograms	




Light and electrical data


Light source	LED
Luminous flux LED [lm]	5320/16338
LED power [W]	40/118
Luminaire luminous flux [lm]	16460
Power of luminaire [W]	175
Luminaire's light efficiency [lm/W]	94
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	4
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	35000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard (E)

Mechanical data

Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1170 x 1043 x 80÷90




A graph of light



Accessories


Index 6E1-500OKW1P-3

Name Suspension New Type-J 34 lenght
1,5m cable 3X 1-point



Index 6E1-8670-B-1,5

Name Suspension New Type-E lenght-
1,5 m without cable 1-point



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%.
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 02-06-2020