


Square format fix downlight from the TROLL family Basic.

DESCRIPTION

Square format fix downlight from the TROLL family Basic setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Designed for wall or ceiling surface mounted. Luminaire body built in die-cast aluminium finished in white. Optical group is IP44. Luminaire built-in an Polycarbonate opal diffuser with an angle beam of 120°. Luminaire sets a 24 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 1517 Lm, with an efficiency of 63,2 Lm/W and a total consumption of 24 W. The average life for the luminaire is 35000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	0450L/M383S/33
Product type	IN
Category	Surface Downlights
Family	Basic
Subfamily	Basic S
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a Polycarbonate opal diffuser.
Installation instructions	Luminaire designed for wall or ceiling surface mounted.
Pictograms	




Dimensions

Product dimensions (mm)	230 x 230 x 48
Packing dimensions (mm)	235 x 235 x 50
Net weight (g)	1385
Gross weight (Kg)	1,32

Scheme

Scheme



Product

Real power (W)	24
Real luminous flux (Lm)	1517
Luminous efficiency (Lm/W)	63,2
Beam angle (°)	120
Life time (h)	35000
IP	44
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,94

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	22
Nominal luminous flux (Lm)	1821
Colour temperature (K)	3000
CRI	80

Photometry

Photometry

