

## BERN LED m1000

24 V LED, 2440lm, PC Tropol® (fracture proof), 840/4000K, narrow beam, external transformer

Article No: 531 429 24 00

LED

IP 66

IP 67

IP 68 20m

IP 69K

CE


III


D

IK 10 PC



illustration may differ



 narrow beam

### DIMENSIONS

L	B	H	a	b	max. weight
1260 mm	95 mm	90 mm	1120 mm	-	2.9 kg

### DESCRIPTION

Tubular luminaire with LED lamps, resistant to pressurised water. Polymer luminaire tube (Ø 60 mm). With internal, anodised aluminium reflector. Eccentric locking technology for easy opening with retractable handle on face side. With hexagon socket screw to prevent unauthorised opening. Ready for connection. Mounting with two stainless steel/polymer mounting clamps.

created on: 2018-11-20 (ext.) Subject to technical changes without prior notice

# BERN LED m1000

24 V LED, 2440lm, PC Tropol® (fracture proof), 840/4000K, narrow beam, external transformer

Article No: 531 429 24 00

## CHARACTERISTICS

Version	m1000	Lamp power	1 x 24 W
Lamp	LED	System power	24 W
Lamp service life	L80 B10 > 60.000 h at +40°C	Colour temperature	White, 840/4000 K, Ra > 80
Extreme-temperature	-40°C to +40°C	Luminous flux lamp	2440 lm
Number of lamps	1-lamp	Protection class	III
Cover material	polymer	IP-rating	IP66, IP67, IP68 20m, IP69K
Colour housing	None	Type of gear	LED operating device voltage-controlled, 24 V - 24 V DC
Cover	protection tube	Through-wiring	without
Light distribution	narrow beam	Through-wiring (optional)	YES
		Impact strength	IK10
		Installation type	wire suspension, Cable suspension, ceiling mounting, wall mounting

## DIAGRAMS

