



L	1265 mm
A	235 mm
H	135 mm

### ILLUMINOTECHNICAL CHARACTERISTICS

Luminous efficiency 100%.  
 Initial luminous flux of the luminaire 11820 lm.  
 Symmetrical elliptical hyperconcentrated distribution.  
 Installation Interdistance Transv.D = 0.48 x hu - Long.D = 0.63 x hu.  
 UGR <19 (EN 12464-1).  
 Luminous efficacy 126 lm/W.  
 Lifetime (L93/B10): 30000 h. (tq+25°C)  
 Lifetime (L90/B10): 50000 h. (tq+25°C)  
 Lifetime (L85/B10): 80000 h. (tq+25°C)  
 Lifetime (L80/B10): 100000 h. (tq+25°C)  
 Lifetime (L85/B10): 50000 h. (tq+45°C)  
 Sudden decreased luminous flux after 50000 hours: 0% (C0).  
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).  
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

### SOURCE

2 linear LED modules 45W/840.  
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).  
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.  
 CCT nominal colour temperature 4000 K.  
 Colour initial tolerance (MacAdam): SDCM 3.

### MECHANICAL CHARACTERISTICS

Single-piece housing in pressed steel, powder-coated in white epoxy-polyester.  
 Polycarbonate screen etched internally, V2 self-extinguishing, UV stabilised, injection moulded.  
 Ecologic anti-aging injected sealing gasket.  
 Oversized gear-tray reflector unit in highly reflective white painted hot-galvanised steel.  
 PMMA lenses with external flat surface.  
 Galvanised steel safety snap-lock clips for diffuser mounting.  
 Dimensions: 1265x235 mm, height 135 mm. Weight 7.53 kg.  
 IP65 protection degree.  
 Mechanical strength to impacts IK10 (20 joule).  
 Glow-wire test resistance 850°C.

### ELECTRICAL CHARACTERISTICS

Halogen Free electronic wiring 230V-50/60Hz, power factor >0.95, constant output current, class I, 1 driver.  
 Power of the luminaire 94 W.  
 ENEC - CE.  
 Flicker: <4%.  
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.  
 Ambient temperature from -20°C to +45°C.  
 Temperature class T6 max 85°C.  
 Quick connection.  
 Relative humidity UR: <85%.

### INSTALLATION

Ceiling / Suspended / Wall.  
 Recommended minimum installation height: 4 metres from the ground.  
 All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com).

### APPLICATIONS

Product suitable for installation in food-production/processing environments (HACCP, IFS, BRC Standard).  
 In industrial environments, stores and dry, dusty indoor environments, subject to occasional water splashes.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).