

PRODUCT FAMILY DATASHEET

OUTDOOR BOLLARD LANTERN

Contemporary bollards with light guide for low-glare illumination



AREAS OF APPLICATION

- Outdoor
- Pathway lighting
- Driveways

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Special light guide design for low-glare illumination

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Diffuser made of opal polycarbonate with transparent polycarbonate cover




TECHNICAL DATA

	Electrical data	Photometrical data	Light technical data	Dimensions & weight			Colors & materials	Temperatures & operating conditions	Lifespan	
Product description	Nominal wattage	Luminous flux	Beam angle	Diameter	Height	Product weight	Product color	Ambient temperature range	Lifespan L70 at 25 °C	Lifespan L80 at 25 °C
O BOLLARD 500 LANTERN 12 W 3000 K IP54 GY	12.00 W	610 lm	210.00 °	110.0 mm	500.0 mm	1900.00 g	Gray	-20...40 °C	30000 h	- h
O BOLLARD 900 LANTERN 12 W 3000 K IP54 GY	12.00 W	610 lm	210.00 °	110.0 mm	900.0 mm	3100.00 g	Gray	-20...40 °C	30000 h	- h


Product description	Lifespan L90 at 25 °C	Additional product data		Capabilities	Certificates & standards		
		Mounting type	Mounting location	Dimmable	Type of protection	Protection class	Protection class IK (shock resistance)
O BOLLARD 500 LANTERN 12 W 3000 K IP54 GY	- h	Surface	Ground	No	IP54	I	IK06
O BOLLARD 900 LANTERN 12 W 3000 K IP54 GY	- h	Surface	Ground	No	IP54	I	IK06

Product description	Glow Wire Test according to IEC 695-2-1	Photobio. safety group acc. to EN62471	Standards
O BOLLARD 500 LANTERN 12 W 3000 K IP54 GY	-	RG 0	CE
O BOLLARD 900 LANTERN 12 W 3000 K IP54 GY	-	RG 0	CE




O BOLLARD 500 LANTERN 12 W 3000 K
IP54 GY

O BOLLARD 900 LANTERN 12 W 3000 K
IP54 GY



O BOLLARD 500 LANTERN 12 W 3000 K
IP54 GY



O BOLLARD 900 LANTERN 12 W 3000 K
IP54 GY

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075074859	O BOLLARD 500 LANTERN 12 W 3000 K IP54 GY	Shipping carton box 2	405 mm x 205 mm x 555 mm	46.08 dm ³	4618.00 g
4058075074873	O BOLLARD 900 LANTERN 12 W 3000 K IP54 GY	Shipping carton box 2	405 mm x 205 mm x 955 mm	79.29 dm ³	7509.00 g

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	------------------------------	--------------------------------------	--------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.