

Datasheet

Bulkhead 360 LED DALI Emergency



CAT NO. 664164/D, 664165/D



664164/D



664165/D

Specifications		
Cat. No.	664164/D	664165/D
Description	Bulkhead R 360 plain LED 4K DALI	Bulkhead R 360 guard LED 4K DALI
Design	Plain	Guard
Diameter (mm)	360	
Depth (mm)	145	
Weight (kg)	4.8	4.9
Operating mode	Switched Maintained	
Module luminous flux (lm)	2700	
Energy consumption (emergency pack only)	4.8W hrc / 2.5W lrc	
Module wattage	18W	
Classification	C0/C90 D50/D50	
Colour temperature (K)	4000	
Power factor	>0.9	
Supply voltage	240V 50Hz	
Driver type	Fixed output/Non-dimmable	
Operating temperature	10°C to 40°C	
IP rating	IP65	
Impact rating	IK10	
Body construction	Die-cast aluminium	
Diffuser	Frosted polycarbonate	
Geartray	High reflective white powder coated mild steel	
Compliance	IEC 62385 AS/NZS 2293 AS/NZS 60598   	
Battery pack	1x5 C 4Ah NiMH	

*hrc- high rate charge, lrc- low rate charge

Datasheet

Bulkhead 360 LED DALI Emergency

CAT NO. 664164/D, 664165/D




664164/D



664165/D

- 18W LED, 4,000K colour temperature module
- L70 @ 50,000 hours
- CRI >80
- Robust die-cast aluminium construction
- IP65 protection
- Frosted diffuser
- Available in plain or guard
- IK10 impact resistant
- DALI computer monitored
- Manufactured in Australia

Dimensions



Legrand Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

HPML1145/B

04_2017