
The perfect blend of technology and design, with sophistication and simplicity. Efficiency, long lifespan, stable light flow and immediate regulation response. Specifically created for high voltage and high efficiency applications.



Made in extruded aluminium protective clear glass.
Stainless steel screens. Die cast end caps.

Applications

Canal S offers a infinity of models that give architects and lighting designer's unlimited inspiration and freedom when creating lighting scene in a wide range of situations.

- Wall-washer: functions as a projector, from inside or outside the building.

- Spot projector due to its power, with medium beam.

The Canal S luminaire projects light up to 45 meters.

This allows illumination and highlighting architectural features of great height such as columns, ribs and projections, giving a new illuminations dimension, impossible before.

- Luminescent buildings. It can be used between the facade and the second skin of the building; this creates an enormous edifice of light, with beams flowing out of the building, generating luminosity and life.



Power

LED 10,3W, 20,7W, 31,5W, 41,4W, 39,6W, 59,4W, 78,3W

Beam

LED 25° (Other optics on request)

Colour temperature

6500K cool white - CRI ≥ 80 (Other colour temperatures on request)

Nominal flux

10,3W - 713lm, 20,7W - 1427lm, 31,5W - 2140lm
41,4W - 2854lm, 39,6W - 2854lm, 59,4W - 4282lm, 78,3W - 5710lm

Nominal lumen output

Electronic (EL) (Other outputs on request)

IP

IP65 - IK08

Finishes

Grey

Supply voltage

220...230V, 50/60Hz

Installation

Floor, wall

Features




Versions:

- LED colours: Warm white 3000°K, Neutral white 4000°K, RGB, on request
- Beam type: Narrow 9°, Wide 45°, Elliptical 9°x45°, on request
- Regulation: DALI, DMX, PWM, on request

LED

Zenithal bracket included
(2 units)

LED and
control gear included



10,3W
25°
365mm
713lm
6500K **LD139503604000**

20,7W
25°
1427lm
6500K **LD139506504000**


31,5W
25°
2140 lm
6500K **LD139509504000**

41,4W
25°
2854 lm
6500K **LD139512504000**

LED

Zenithal bracket included
(2 units)

LED and
control gear included




39,6W
25°
2854lm
6500K **LD101506804000**

59,4W
25°
4282 lm
6500K **LD101509804000**

78,3W
25°
5710 lm
6500K **LD101512704000**

The Canal range of LED linear fixtures can be recessed into any surface indoors or outdoors, also into paving. Canal is an excellent solution to provide nearby surfaces with a wash of light, in colour if required.



Grand Hyatt Cairo, Egypt

Power

LED 9W, 18W, 27W

Beam

LED 8°, 60°, 15° x 90°

Colour temperature

3000K warm white - CRI ≥ 80
4000K neutral white - CRI ≥ 80

Nominal lumen output

LED 9W - 500 lm, 18W - 1000 lm, 27W - 1500 lm

Control gear

Electronic (EL)

IP

IP67 - IK08

Finishes

Inox


Supply voltage

220... 240V, 50/60Hz


Installation

Recessed

Features



LED and control gear included



9W L= 402
 18W L= 699
 27W L= 996

9W	9W	9W
8°	60°	15° x 90°
500 lm	500 lm	500 lm
3000K 11.1693.1831.20	3000K 11.1693.1832.20	3000K 11.1693.1833.20
4000K 11.1693.1841.20	4000K 11.1693.1842.20	4000K 11.1693.1843.20

18W	18W	18W
8°	60°	15° x 90°
1000 lm	1000 lm	1000 lm
3000K 11.1693.2831.20	3000K 11.1693.2832.20	3000K 11.1693.2833.20
4000K 11.1693.2841.20	4000K 11.1693.2842.20	4000K 11.1693.2843.20

27W	27W	27W
8°	60°	15° x 90°
1500 lm	1500 lm	1500 lm
3000K 11.1693.3831.20	3000K 11.1693.3832.20	3000K 11.1693.3833.20
4000K 11.1693.3841.20	4000K 11.1693.3842.20	4000K 11.1693.3843.20