



PRODUCT DETAILS



Dimensions



Accessories



CAPRIOLA

CAPRIOLA S ASYMMETRIC LED

10500lm/750 1x80W, FIX, RAL 9017

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Wall mounted/pole-top installation (W/P)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Asymmetric lenses (LAS)
BEAM ANGLE	ASYM
WIRING	Electronic control gear FIX (ECG) External lead-in flexible cable
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium
SURFACE FINISH	Housing: black RAL 9017 (B17)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,96
NET LUMEN OUTPUT (Ta=25°C)	10500 lm
POWER CONSUMPTION	80 W
SYSTEM EFFICACY	131 lm/W
CORRELATED COLOUR TEMPERATURE	5000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	3 SDCM
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L70 / B50
AMBIENT OPERATING TEMPERATURE	From -30 °C to +40 °C
IP PROTECTION DEGREE	IP66
MECHANICAL IMPACT RESISTANCE	IK08
DIMENSIONS (L x W x H)	308 x 82 x 359 mm
WEIGHT	4,6 kg

AREAS OF APPLICATION INDUSTRY AND ENGINEERING



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.