



## PRODUCT DETAILS



## Dimensions



## Accessories



# CAPRIOLA

**CAPRIOLA S ASYMMETRIC LED 7500lm/750  
1x60W, FIX, RAL 9017**

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)


## Description

<b>MOUNTING</b>	Wall mounted/pole-top installation (W/P)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Asymmetric lenses (LAS)
<b>BEAM ANGLE</b>	ASYM
<b>WIRING</b>	Electronic control gear FIX (ECG) External lead-in flexible cable
<b>MATERIALS</b>	Cover: transparent hardened glass Housing: die-cast aluminium
<b>SURFACE FINISH</b>	Housing: black RAL 9017 (B17)
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	0,96
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	7500 lm
<b>POWER CONSUMPTION</b>	60 W
<b>SYSTEM EFFICACY</b>	125 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	5000 K
<b>COLOUR RENDERING INDEX</b>	>70 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L70 / B50
<b>AMBIENT OPERATING TEMPERATURE</b>	From -30 °C to +40 °C
<b>IP PROTECTION DEGREE</b>	IP66
<b>MECHANICAL IMPACT RESISTANCE</b>	IK08
<b>DIMENSIONS (L x W x H)</b>	308 x 82 x 359 mm
<b>WEIGHT</b>	4,5 kg

## AREAS OF APPLICATION INDUSTRY AND ENGINEERING



## LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.