




| Dimensions              |          |
|-------------------------|----------|
| Product dimensions (mm) | Ø87 x 91 |
| Net weight (g)          | 450      |
| Gross weight (Kg)       | 0,53     |
| Drilling hole (mm)      | Ø 75     |

| Scheme |  |
|--------|--|
| Scheme |  |



### Adjustable round downlight from the TROLL family Contract.

#### DESCRIPTION

Adjustable round downlight from the TROLL family Contract setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium finished in white. Optical group is IP44 on the visible frontal area. Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector. with an angle beam of 30°. Luminaire sets a 7 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Luminaire sets a ball joint system which allows rotation 355° and tilting 30°. Fixture has a luminous flux of 750 Lm, with an efficiency of 83,3 Lm/W and a total consumption of 9 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

| Product                     |                    |
|-----------------------------|--------------------|
| Real power (W)              | 9                  |
| Real luminous flux (Lm)     | 750                |
| U.G.R. (%)                  | < 19               |
| Luminous efficiency (Lm/W)  | 83,3               |
| Beam angle (°)              | 30                 |
| Life time (h)               | 50000              |
| IP                          | 44/20              |
| Electrical class insulation | Class 2            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | White              |
| Energy efficiency class     | A                  |

| Control gear          |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |
| Factor de potencia    | 0,99                    |

| Light source               |      |
|----------------------------|------|
| Light source included      | Yes  |
| Light source               | Led  |
| Nominal power (W)          | 7    |
| Nominal luminous flux (Lm) | 900  |
| Colour temperature (K)     | 4000 |
| Colour consistency (SDCM)  | 3    |
| CRI                        | 80   |

| Accesories      |                        |
|-----------------|------------------------|
| 11.1603.0012.04 | Honeycomb mesh for 7W. |
| 11.1603.0111.04 | Reflector for 7W.      |
| 11.1603.0111.33 | Reflector for 7W.      |

|                           |  |
|---------------------------|--|
| Item code                 | 11.1601.1844.33  |
| Product type              | IN   |
| Category                  | Recessed Downlights  |
| Family                    | Contract   |
| Subfamily                 | Contract A   |
| Materials                 | Luminaire body built in die-cast aluminium.  |
| Optical system            | Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector.. |
| Installation instructions | Luminaire designed for ceiling recessed installation.  |

#### Pictograms

