



Accessories




**DALYA IOT S (L01) LED 4900lm/740
1x41W, EDO, RAL 9006**

- Certificates
- Datasheet
- Product sheet
- Installation manual
- IES file
- LDT file
- EEC

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (L01) On request L02, L03, L04, L05, L06, L07, L08, L09, L10, L11, L12, L18
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear DALI + CONSTANT LUMEN OUTPUT (EDO)
MATERIALS	Cover: transparent hardened glass Frame: sheet steel Housing: die-cast aluminium Tilttable spigot: die cast aluminium (on request ø76)
SURFACE FINISH	Housing: grey RAL 9006 (G06)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,96
NET LUMEN OUTPUT (Ta=25°C)	4900 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION INITIAL	41 W
POWER CONSUMPTION END	45 W
SYSTEM EFFICACY	120 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	5 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L100 / B10
AMBIENT OPERATING TEMPERATURE	From -40 °C to +50 °C
IP PROTECTION DEGREE	IP66
MECHANICAL IMPACT RESISTANCE	IK09
WINDAGE AREA SIDE / TOP	0.039/0.140 m²
RECOMENDED MOUNTING HEIGHT	5-8 m

LIDC



DIMENSIONS (L x W x H)

573 x 277 x 93 mm

WEIGHT

8,2 kg

AREAS OF APPLICATION

 STREET AND URBAN



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.