



PRODUCT DETAILS



Dimensions



Accessories



DALYA M

**DALYA M (L01) LED 2200lm/740 1x17W,
FIX-ECC, RAL 9006**


DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (L01) On request: L02, L03, L04, L05, L06, L07, L08, L09, L10, L11, L12, L18
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX + CONSTANT LUMEN OUTPUT (ECC)
MATERIALS	Cover: transparent hardened glass Frame: sheet steel Housing: die-cast aluminium Tilttable spigot: die cast aluminium Housing: grey RAL 9006 (G06)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2200 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION INITIAL	17 W
POWER CONSUMPTION END	19 W
SYSTEM EFFICACY	129 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	5 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L100 / B10
AMBIENT OPERATING TEMPERATURE	From -40 °C to +45 °C
IP PROTECTION DEGREE	IP66
MECHANICAL IMPACT RESISTANCE	IK10
WINDAGE AREA SIDE / TOP	0.047/0.154 m²
RECOMENDED MOUNTING HEIGHT	5-8 m

LIDC



REPLACEMENT OF STANDARD

HPS 70 W

DIMENSIONS (L x W x H)

753 x 281 x 95 mm

WEIGHT

9,4 kg

AREAS OF APPLICATION

 STREET AND URBAN



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.