




## PRODUCT DETAILS



## Dimensions



## Accessories



# DALYA S

**DALYA S (L01) LED 1800lm/740 1x15W,  
FIX-ECC, RAL 9006**

## DOWNLOADS


[Certificates](#)  
[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Pole top / side entry installation (PMT)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Lenses (L01) On request: L02, L03, L04, L05, L06, L07, L08, L09, L10, L11, L12, L18
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	External lead-in flexible cable Electronic control gear FIX + CONSTANT LUMEN OUTPUT (ECC)
<b>MATERIALS</b>	Cover: transparent hardened glass Frame: sheet steel Housing: die-cast aluminium Tilttable spigot: die cast aluminium Housing: grey RAL 9006 (G06)
<b>SURFACE FINISH</b>	
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	1800 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION INITIAL</b>	15 W
<b>POWER CONSUMPTION END</b>	16 W
<b>SYSTEM EFFICACY</b>	120 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	>70 Ra
<b>COLOUR TOLERANCE</b>	5 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	II
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	100,000 hours / L100 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -40 °C to +50 °C
<b>IP PROTECTION DEGREE</b>	IP66
<b>MECHANICAL IMPACT RESISTANCE</b>	IK09
<b>WINDAGE AREA SIDE / TOP</b>	0,035 / 0,140 m <sup>2</sup>
<b>RECOMENDED MOUNTING HEIGHT</b>	5-8 m



## LIDC



**DIMENSIONS (L x W x H)**

651 x 277 x 93 mm

**WEIGHT**

8,2 kg

**AREAS OF APPLICATION**

 STREET AND URBAN



5 YEARS  
WARRANTY



EEC  
A++/A+/A



HEAT  
SINK



MAINTENANCE  
FREE



UV/IR



ECO  
FRIENDLY



ENERGY  
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.