PRODUCT DETAILS

Dimensions



Accessories

DALYA S

DALYA S (L01) LED 4900lm/740 1x41W, FIX-ECC, RAL 9006

DOWNLOADS

Certificates
Datasheet
Product sheet
Installation manual
IES file
LDT file
EEC

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (L01) On request: L02, L03, L04, L05, L06, L07, L08, L09, L10, L11, L12, L18
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX + CONSTANT LUMEN OUTPUT (ECC)
MATERIALS	Cover: transparent hardened glass Frame: sheet steel Housing: die-cast aluminium Tiltable spigot: die cast aluminium
SURFACE FINISH	Housing: grey RAL 9006 (G06)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	4900 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION INITIAL	41 W
POWER CONSUMPTION END	45 W
SYSTEM EFFICACY	120 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	5 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L100 / B10
AMBIENT OPERATING TEMPERATURE	From -40 °C to +50 °C
IP PROTECTION DEGREE	IP66
MECHANICAL IMPACT RESISTANCE	IK09
WINDAGE AREA SIDE / TOP	0,035 / 0,140 m²
RECOMENDED MOUNTING HEIGHT	5-8 m

LIDC



DIMENSIONS (L x W x H)	651 x 277 x 93 mm
WEIGHT	8,2 kg

AREAS OF APPLICATION STREET AND URBAN

5 YEARS WARRANTY · EEC A++/A+/F · HEAT SINK · MAINTENANCE FREE · UV/IR · ECO FRIENDLY · ENERGY SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.