


## PRODUCT DETAILS



## Dimensions



## Accessories



# DECLAN II SUR./SUS.

**DECLAN II SUR./SUS. SS1 LED 3800lm/840  
1x33W, FIX, RAL 9003**

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description


<b>MOUNTING</b>	Surfaced / Suspended (SS1)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Diffuser + reflector (MCL)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: polished metallised polycarbonate Housing: white RAL 9003 (W03)
<b>SURFACE FINISH</b>	Suspended version - rope suspension
<b>ACCESSORIES</b>	220-240 V, 50-60 Hz
<b>VOLTAGE</b>	> 0,95
<b>POWER FACTOR</b>	3800 lm
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	33 W
<b>POWER CONSUMPTION</b>	115 lm/W
<b>SYSTEM EFFICACY</b>	4000 K
<b>CORRELATED COLOUR TEMPERATURE</b>	80 Ra
<b>COLOUR RENDERING INDEX</b>	3 SDCM
<b>COLOUR TOLERANCE</b>	A++ / A+ / A
<b>EEC</b>	I
<b>PROTECTION CLASS</b>	Passive
<b>THERMAL MANAGEMENT</b>	50,000 hours / L80 / B10
<b>SERVICE LIFETIME (Ta=25°C)</b>	From -20 °C to +40 °C
<b>AMBIENT OPERATING TEMPERATURE</b>	IP20
<b>IP PROTECTION DEGREE</b>	600 x 600 x 36 mm
<b>DIMENSIONS (L x W x H)</b>	7,1 kg
<b>WEIGHT</b>	

## AREAS OF APPLICATION

**EDUCATION**  
 **HEALTH AND CARE**  
 **OFFICE**



## LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.