


PRODUCT DETAILS



Dimensions



Accessories



DECLAN II SUR./SUS.

**DECLAN II SUR./SUS. SS4 LED 3700lm/830
1x33W, FIX, RAL 9003**

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Surfaced / Suspended (SS4)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Diffuser + reflector (MCL)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: polished metallised polycarbonate Housing: white RAL 9003 (W03)
SURFACE FINISH	Suspended version - rope suspension
ACCESSORIES	220-240 V, 50-60 Hz
VOLTAGE	> 0,95
POWER FACTOR	3700 lm
NET LUMEN OUTPUT (Ta=25°C)	33 W
POWER CONSUMPTION	112 lm/W
SYSTEM EFFICACY	3000 K
CORRELATED COLOUR TEMPERATURE	80 Ra
COLOUR RENDERING INDEX	3 SDCM
COLOUR TOLERANCE	A++ / A+ / A
EEC	I
PROTECTION CLASS	Passive
THERMAL MANAGEMENT	50,000 hours / L80 / B10
SERVICE LIFETIME (Ta=25°C)	From -20 °C to +40 °C
AMBIENT OPERATING TEMPERATURE	IP20
IP PROTECTION DEGREE	1200 x 300 x 36 mm
DIMENSIONS (L x W x H)	7,4 kg
WEIGHT	


AREAS OF APPLICATION EDUCATION

HEALTH AND CARE

OFFICE



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.