

PRODUCT FAMILY DATASHEET

OUTDOOR FACADE BELT

Luminaires with modern design and light outlet up and down



AREAS OF APPLICATION

- Outdoor
- Building facades
- Entrance lighting

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in round and square form
- Diffuser made of opal PMMA




TECHNICAL DATA


Product description	Electrical data	Photometric data	Light technical data	Dimensions & weight				Colors & materials	Temperatures & operating conditions	Lifespan
	Nominal wattage	Luminous flux	Beam angle	Length	Width	Height	Product weight	Product color	Ambient temperature range	Lifespan L70 at 25 °C
O FACADE BELT RD 11 W 3000 K IP54 GY	11.00 W	400 lm	335.00 °	60.0 mm	240.0 mm	142.0 mm	720.00 g	Gray	-20...40 °C	30000 h
O FACADE BELT SQ 11 W 3000 K IP54 GY	11.00 W	410 lm	340.00 °	60.0 mm	240.0 mm	142.0 mm	750.00 g	Gray	-20...40 °C	30000 h

Product description	Lifespan L80 at 25 °C	Lifespan L90 at 25 °C	Additional product data		Capabilities	Certificates & standards	
			Mounting type	Mounting location	Dimmable	Type of protection	Protection class
O FACADE BELT RD 11 W 3000 K IP54 GY	- h	- h	Surface	Wall	No	IP54	I
O FACADE BELT SQ 11 W 3000 K IP54 GY	- h	- h	Surface	Wall	No	IP54	I

Product description	Protection class IK (shock resistance)	Glow Wire Test according to IEC 695-2-1	Photobio. safety group acc. to EN62471	Standards
O FACADE BELT RD 11 W 3000 K IP54 GY	IK06	-	RG 0	CE
O FACADE BELT SQ 11 W 3000 K IP54 GY	IK06	-	RG 0	CE



O FACADE BELT RD 11 W 3000 K IP54
GY



O FACADE BELT SQ 11 W 3000 K IP54
GY

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075074972	O FACADE BELT RD 11 W 3000 K IP54 GY	Shipping carton box 6	600 mm x 220 mm x 290 mm	38.28 dm ³	5616.00 g
4058075074996	O FACADE BELT SQ 11 W 3000 K IP54 GY	Shipping carton box 6	600 mm x 220 mm x 290 mm	38.28 dm ³	5796.00 g

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	------------------------------	--------------------------------------	--------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.