




Data Sheet

G2 LED Slide Connect DALI Emergency

CAT NO. 686200/D, 686208/D, 686206/D



Specifications			
Cat No	686200/D	686206/D	686208/D
Description	White body c/w running man sheets (set of 4) DALI	Black body no downward lens c/w running man sheets (set of 4) DALI	Silver body c/w running man sheets (set of 4) DALI
Lamp	1x1W LED		
Battery	NiMH 2x2 Sub-C cells – 4.8 Vdc 2Ah		
Operating Voltage	240V a.c. +/- 6% 50Hz		
Power Consumption	3W hrc/ 1.9W lrc		
Body Construction	ABS		
Operating Temperature	10° to 40°		
IP Rating	IP20		
Compliance	IEC 62385 AS/NZS 2293 AS/NZS 60598   		

*hrc- high rate charge, lrc- low rate

G2 LED Slide Connect DALI Emergency

CAT NO. 686200/D, 686208/D, 686206/D



- Low energy consumption and heat dissipation – save up to 70% on energy consumption*
- Unique single LED maintained exit sign (patent pending)
- Long life LED light source - up to 50,000 hours
- High resistance polycarbonate clear cover and white ABS housing
- One box solution
- Can be wall, ceiling or cantilever mounted
- High temperature NiMH batteries
- Large terminal block for ease of connection
- DALI monitored
- Low cost maintenance
- Available in White, Silver and Black body
- Manufactured in Australia

Accessories	
Cat No.	Description
686215	Cantilever bracket, White
686216	Wire suspension kit, silver pair of 2
686231	Mounting bracket
686235	Wire guard single sided
686236	Wire guard double sided

Classification		
Catalogue No.	Ceiling Mount	
Cat No.	C ₀	C ₉₀
686200/D	D5	C20

* When compared with traditional fluorescent fitting

Legrand - Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or
Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.