


PRODUCT DETAILS



Dimensions



Accessories



GACRUX XTP

GACRUX XTP PV-1 MICROPRISMA LED
3100lm/830 1x35W, FIX, RAL 9003

DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Ceiling recessed PVx - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) External lead-in flexible cable
MATERIALS	Diffuser: PMMA Frame: sheet steel Housing: sheet steel Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3100 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	35 W
SYSTEM EFFICACY	89 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP54
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS (L x W x H)	PV1: 597 x 597 x 110 mm
WEIGHT	8,1 kg

AREAS OF APPLICATION

EDUCATION
HOSPITALITY

LIDC



HOUSE AND FLAT

HEALTH AND CARE

OFFICE



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.