


PRODUCT DETAILS



Dimensions



Accessories



GACRUX XTP

**GACRUX XTP PV-1 OPAL LED 3800lm/840
1x35W, FIX, RAL 9003**

DOWNLOADS


[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed PVx - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) External lead-in flexible cable
MATERIALS	Diffuser: PMMA Frame: sheet steel Housing: sheet steel Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3800 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	35 W
SYSTEM EFFICACY	109 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP54
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS (L x W x H)	PV1: 597 x 597 x 110 mm
WEIGHT	8,1 kg

AREAS OF APPLICATION EDUCATION
 HOSPITALITY

LIDC



HOUSE AND FLAT

HEALTH AND CARE

OFFICE



ECO FRIENDLY



ENERGY SAVING



HEAT SINK



MAINTENANCE FREE



UV/IR

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.