


PRODUCT DETAILS



Dimensions



Accessories



GACRUX XTP

**GACRUX XTP PR-4 OPAL LED 3400lm/830
1x35W, FIX, RAL 9003**

DOWNLOADS


[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed PRx - T-ceiling
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) External lead-in flexible cable
MATERIALS	Diffuser: PMMA Frame: sheet steel Housing: sheet steel Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3400 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	35 W
SYSTEM EFFICACY	97 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP54
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS (L x W x H)	PR4: 1245 x 312 x 130 mm
WEIGHT	9,6 kg

AREAS OF APPLICATION  EDUCATION
 HOSPITALITY

LIDC



 HOUSE AND FLAT

 HEALTH AND CARE

 OFFICE



ECO FRIENDLY



ENERGY SAVING



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.