




PRODUCT DETAILS



Dimensions



Accessories



GRAFIAS RECESSED

**GRAFIAS RECESSED 80° LED 10400lm/840
1x94W, FIX, -**


DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

| | |
|--------------------------------------|---|
| MOUNTING | Ceiling recessed |
| LIGHT SOURCE | LED |
| OPTICAL SYSTEM | Polished reflector (PRE) |
| BEAM ANGLE | 80° |
| LIGHT DISTRIBUTION | Direct |
| WIRING | Electronic control gear FIX (ECG) |
| MATERIALS | Cover: transparent hardened glass Housing: die-cast aluminium Reflector: evaporative coated PC Mounting plate: sheet steel Mounting plate: white RAL 9003 (W03) |
| SURFACE FINISH | Safety wires |
| ACCESSORIES | 220-240 V, 50-60 Hz |
| VOLTAGE | > 0,95 |
| POWER FACTOR | 10400 lm |
| NET LUMEN OUTPUT (Ta=25°C) | +/- 10 % |
| LUMINOUS FLUX TOLERANCE | 94 W |
| POWER CONSUMPTION | 111 lm/W |
| SYSTEM EFFICACY | 4000 K |
| CORRELATED COLOUR TEMPERATURE | 80 Ra |
| COLOUR RENDERING INDEX | 5 SDCM |
| COLOUR TOLERANCE | A++ / A+ / A |
| EEC | I |
| PROTECTION CLASS | Passive |
| THERMAL MANAGEMENT | 50,000 hours / L80 / B10 |
| SERVICE LIFETIME (Ta=25°C) | From -40 °C to +40 °C |
| AMBIENT OPERATING TEMPERATURE | IP66 |
| IP PROTECTION DEGREE | The luminaire is not suitable for use in outdoor applications |
| WARNING | MECHANICAL IMPACT RESISTANCE IK07 |
| DIMENSIONS (L x W x H) | 565 x 425 x 92 mm |
| OPENING (L x W) | 510 x 390 mm |

LIDC



WEIGHT

10 kg

AREAS OF APPLICATION

 SPORT AND LEISURE

 INDUSTRY AND ENGINEERING

 RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.