


PRODUCT DATASHEET

HIGH BAY LED PRO 120 W 4000 K 90° GEN2

LEDVANCE HIGH BAY PRO | LED high-bay luminaires



AREAS OF APPLICATION

- Industrial and storage facilities
- Production and assembly facilities
- Shopping malls
- Supermarkets
- Loading docks, access areas
- Aircraft hangers
- Train stations
- Airports, stations

PRODUCT BENEFITS

- Equipment for suspended and pole mounting included
- Unique heat sink design with air channels to increase system reliability
- Low maintenance and operation costs due to long lifetime of LED
- Single piece lens, color stable and shape-retaining even at high temperatures
- High efficiency and reliability

PRODUCT FEATURES

- Four versions with different luminous flux available
- Luminous efficacy: up to 135 lm/W
- Lifetime: up to 50,000 h
- Beam angle: 90°×90° or 70°×70°
- Color rendering index R_a : ≥ 80
- Power factor: > 0.9
- Impact resistance: IK08



- Type of protection: IP65
- Robust die-cast aluminum housing

TECHNICAL DATA

Electrical data

Nominal wattage	120.00 W
Nominal voltage	220...240 V
Power factor λ	> 0.90
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Luminous efficacy	135 lm/W
Luminous flux	16200 lm
Standard deviation of color matching	≤ 5 sdcn
Light color (designation)	Cool White
Color rendering index Ra	80

Light technical data

Beam angle	90 °
------------	------

— Dimensions & weight

Diameter	285.0 mm
Height	129.5 mm
Product weight	2700.00 g
Cable length	500 mm

Colors & materials

Body material	Aluminum
Housing color	Black
Product color	Black

Temperatures & operating conditions

Ambient temperature range	-30...50 °C
---------------------------	-------------

Lifespan

Number of switching cycles	50000
----------------------------	-------

Additional product data

Mounting location	Ceiling
-------------------	---------

Capabilities

Dimmable	No
Type of connection	Cable, 3-pole
LED module replaceable	Not replaceable

Certificates & standards

Protection class IK (shock resistance)	IK08
Protection class	I
Type of protection	IP65

EQUIPMENT / ACCESSORIES

- Clips for optional surface mounting available

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075072985	HIGH BAY LED PRO 120 W 4000 K 90° GEN2	Shipping carton box 1	335 mm x 335 mm x 185 mm	20.76 dm ³	3413.00 g

- The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.