


Highline is a range of façade luminaires of minimalistic design. They are available with wall washer, narrow beam or asymmetrical distribution. The fields of application range from accent lighting to uniform wall washing. Highline is a versatile instrument for many different applications, in a uniform and discreet housing.





With narrow beam distribution the luminaires are used for the accent lighting of vertical surfaces.




The narrow beam version produces an intensive grazing effect above the longitudinal axis of the luminaire.

The luminaires are available with 3 different fixing systems:  
a bracket for installation on a façade, a mounting base or a wall arm.








**Highline  
with wall bracket**

With high performance LEDs,  
integral temperature monitoring device,  
CRI: > 80, Colour tolerance: max. 2 SDCM  
Service life: L90/B10 > 50 000 h  
protection class I, IP65 , IK08  
windage area AW 0.029 m<sup>2</sup>  
corrosion-resistant die cast aluminium housing AlSi12,  
polyester powder coated,  
all exterior steel parts are stainless steel,  
tempered safety glass,  
silicon gasket, closure with 2 stainless steel screws,  
wall bracket: 2 elongated holes Ø 6,5 mm,  
spacing 40 mm, tilt range 180°,  
M20 cable gland,  
integral driver (AC/DC)

**Highline, narrow beam**

Part number	Colour	Light source	Luminous flux	Beam angle γ (FWHM)
<b>8 730 146 019</b>	black	9 x LED 2.5 W warm white (3000 K)	1508 lm	6°
<b>8 730 166 019</b>	white			
<b>8 730 156 019</b>	silver grey			





Part number	Colour	Light source	Luminous flux	Beam angle γ (FWHM)
<b>8 730 145 019</b>	black	9 x LED 2.5 W neutral white (4000 K)	1583 lm	6°
<b>8 730 165 019</b>	white			
<b>8 730 155 019</b>	silver grey			



**Highline, wall washer**

Part number	Colour	Light source	Luminous flux	Beam angle γ (FWHM)	
				C 0 – 180	C 90 – 270
<b>8 730 146 009</b>	black	9 x LED 2.5 W warm white (3000 K)	1281 lm	14°	93°
<b>8 730 166 009</b>	white				
<b>8 730 156 009</b>	silver grey				




Part number	Colour	Light source	Luminous flux	Beam angle γ (FWHM)	
				C 0 – 180	C 90 – 270
<b>8 730 145 009</b>	black	9 x LED 2.5 W neutral white (4000 K)	1345 lm	14°	93°
<b>8 730 165 009</b>	white				
<b>8 730 155 009</b>	silver grey				



**Highline, asymmetrical beam**


Part number	Colour	Light source	Luminous flux	Main beam angle γ
<b>8 730 146 089</b>	black	9 x LED 2.5 W warm white (3000 K)	1121 lm	35°
<b>8 730 166 089</b>	white			
<b>8 730 156 089</b>	silver grey			

Part number	Colour	Light source	Luminous flux	Main beam angle γ
<b>8 730 145 089</b>	black	9 x LED 2.5 W neutral white (4000 K)	1177 lm	35°
<b>8 730 165 089</b>	white			
<b>8 730 155 089</b>	silver grey			




Part number	Description
<b>... 0 ...</b>	<b>Luminaire with mounting flange</b> (for horizontal surfaces)

Part number	Description
<b>... 1 ...</b>	<b>Dimmable luminaire (DALI)</b>
<b>... 2 ...</b>	<b>Dimmable luminaire (1-10 V)</b>










**LED**

Luminaires available in 2700 K and other colour temperatures on request



## Highline with wall arm

With high performance LEDs,  
integral temperature monitoring device,  
CRI: > 80, Colour tolerance: max. 2 SDCM  
Service life:: L90/B10 > 50 000 h  
protection class I, IP65 , IK08  
windage area AW 0.035 m<sup>2</sup>  
corrosion-resistant die cast aluminium housing AlSi12,  
polyester powder coated,  
all exterior steel parts are stainless steel,  
tempered safety glass,  
silicon gasket, closure with 2 stainless steel screws,  
mounting plate: 4 drilled holes Ø 7 mm,  
spacing 47 mm, joint with tilt range 180°,  
M20 cable gland,  
integral driver (AC/DC)



### Highline with wall arm, wall washer

Part number	Colour	Light source	Luminous flux	Beam angle γ (FWHM)	
<b>8 730 746 009</b>	black	9 x LED 2.5 W warm white (3000 K)	1281 lm	C 0 – 180	C 90 – 270
<b>8 730 766 009</b>	white			14°	93°
<b>8 730 756 009</b>	silver grey				

Part number	Colour	Light source	Luminous flux	Beam angle γ (FWHM)	
<b>8 730 745 009</b>	black	9 x LED 2.5 W neutral white (4000 K)	1345 lm	C 0 – 180	C 90 – 270
<b>8 730 765 009</b>	white			14°	93°
<b>8 730 755 009</b>	silver grey				

Part number	Description
<b>• • • • • 1 • •</b>	<b>Dimmable luminaire (DALI)</b>
<b>• • • • • 2 • •</b>	<b>Dimmable luminaire (1-10 V)</b>

## LED

Luminaires available in 2700 K and other colour temperatures on request

