

# HISAVER HIGHBAY V3



## FEATURES & BENEFITS

RX Lighting Hisaver Highbay V3 is a 4000K, IP54 rated luminaire, with high performance Nichia SMD chips and a Meanwell driver, and is:

- Multi Wattage -  
100w, 120w, 150w or 200w
- Adjustable Beam Angle -  
Wide Beam 120°  
Medium Beam 90°  
Narrow Beam 65°

These two features allows this luminaire to be used in a very broad range of applications and mounting height options.

The IP54 rating means that it is suitable for indoor or undercover use.

### Optional Accessories.

These include;

- Casambi Wireless Control Module with Motion Sensor - Plug and play.
- 90 Degree Aluminium Reflector.
- Reflector, Polycarbonate with bottom twist lock diffuser.
- Stirrup Mounting Bracket, Adjustable.
- Safety Chain 1.5m length St/Stl.

For technical details, see page 2

## APPLICATIONS

Warehouses, Industrial sites,  
Commercial and Big Box Retail.

## LIFETIME

5 Year Warranty

Operating Temperature -  
-20°C to +40°C

Driver Lifetime -  
50,000hrs at Ta25

SMD Lifetime -  
L80 B10, 80,000hrs  
Calculated

CASAMBI



# HISAVER HIGHBAY V3

ORDER CODE	DESCRIPTION	CARTON QTY	STOCKED ITEM
REXHISLED200WV3	HISAVER LED HIGHBAY 100-200W ADJ POWER 0-10V DIM IP54 V3	EA	YES
REXHBSCHAIN1.5M	HIGHBAY SAFETY CHAIN ONLY 1.5M	1	YES
REXHBPCREFDIF	HIGHBAY PC REFLECTOR WITH DIFFUSER	1	YES
REXHB90ALIREF	HIGHBAY 90 DEGREE ALI REFLECTOR	1	YES
REXHBADJBKTHB12	HIGHBAY ADJUSTABLE BRACKET	1	YES
REXHISCASMMOD	HISAVER CASAMBI WIRELESS CONTROL MODULE	EA	YES

WATTS	100W	120W	150W	200W
LUMEN OUTPUT	15,500lm	18,600lm	23,140lm	28,000lm
EFFICACY	140-155lm/w			
COLOUR TEMPERATURE	4000K			
CRI	CRI >80			
BEAM ANGLE	Adjustable beam angle - Narrow (65°), Medium (90°), Wide (120°)			
IES FILES	Yes			
IP RATING	IP54			
IK RATING	IK07			
LIFETIME	L80 B10 80000hrs			
DIMMABLE	Dimmable - Casambi or 1-10V on request			
WARRANTY	5 Years			
DIMENSIONS	320mm x 168mm (height includes hanger bolt)			
POWER FACTOR	≥0.9			
VOLTAGE & FREQUENCY	230V 50Hz			
WORKING TEMPERATURE	-20°C to +40°C			
WEIGHT	4.0kg			
MATERIALS	Aluminium Body/Heat Sink. Lens is Polycarbonate			
BODY COLOUR	Black			
MOUNTING OPTIONS	Suspended or stirrup mounted via separate accessory			
APPLICABLE STANDARDS	IEC60598 Part 2.1 Fixed General Purpose Luminaires			
CONNECTION	1.5m flex and standard 3 pin plug			