

## HISAVER HIGHBAY



with Motion Sensor

### FEATURES & BENEFITS

The RX Lighting HiSaver LED Highbay is multi-wattage and has 3 selectable beam angles.

Fitting is IP42 which makes it suitable for indoors and undercover installation only.

Optional daylight and motion sensor available. Maximum mounting height of 15 m. Remote control available to allow the sensor control settings to be altered after installation.

Selectable Beam angles; Wide angle, Medium and Narrow beam

High performance Nichia SMD chips and Meanwell driver

For technical details, see page 2

### APPLICATIONS

Shops, Warehouse,  
Commerical, Industrial

### LIFETIME

50,000hrs

Warranty 5 Years



# HIPRO HIGHBAY

ORDER CODE	DESCRIPTION	CARTON QTY
REXHISLED200W	Hisaver LED Highbay 100-200w Adjustable Power & Beam Angle	1
REXHISSENSORM	Plug and Play Motion Sensor For 100w-200w	1
REXHISREMOTE	Remote Control For Motion Sensor	1
REXHBPCREFDIF	HiPro Highbay PC Reflector with Diffuser	1
REXHB90ALIREF	HiPro Highbay 90 Degree Ali Reflector	1
REXHB12ADJBKT45	HiPro Highbay Adjustable Bracket 45degree	1
REXHBSCHAIN1.5M	Hipro Highbay Safety Chain Only 1.5m	1

WATTS	100W	120W	150W	200W
LUMEN OUTPUT	15500lm	18600lm	23250lm	28000lm
EFFICACY	140-155lm/w			
COLOUR TEMPERATURE	4000K			
CRI	Ra >80			
BEAM ANGLE	Adjustable narrow, wide and medium beams			
IP RATING	IP42			
IK RATING	IK07			
IES FILES AVAILABLE	Yes			
DIMMING / CONTROLS / DRIVERS				
LIFETIME	L80 B10 50,000hrs			
WARRANTY	5 years			
DIMENSIONS	320mm diameter (167mm height including hanger bolt)			
POWER FACTOR	≥0.9			
VOLTAGE & FREQUENCY	230V 50/60Hz			
WORKING TEMPERATURE	-30°C ~+ 50°C			
WEIGHT	4.2±0.3kg			
MATERIALS	Aluminum with Polycarbonate Lens			
BODY COLOUR	Black			
MOUNTING OPTIONS	Suspended			
APPLICABLE STANDARD/S	CE, RoHS, SAA			
CONNECTION E.G. FLEX & PLUG / TERMINAL	1.5m flex and standard 3 pin plug			