



PRODUCT DETAILS



Dimensions



Accessories



JORY FLOOD M

JORY FLOOD M 20° LED 1700lm/840

1x20W, FIX, -

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Wall mounted (WMD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Facet reflector (FRE)
BEAM ANGLE	20°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) External lead-in flexible cable
MATERIALS	Cover: transparent hardened glass Housing: die-cast aluminium
SURFACE FINISH	Housing: NHG
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	1700 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
NUMBER OF LAMPS	1
POWER CONSUMPTION	20 W
SYSTEM EFFICACY	85 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L70 / B50
AMBIENT OPERATING TEMPERATURE	From -10 °C to +35 °C
IP PROTECTION DEGREE	IP67
MECHANICAL IMPACT RESISTANCE	IK08
DIMENSIONS (L x H)	126 x 205 mm
WEIGHT	2,6 kg

AREAS OF APPLICATION **STREET AND URBAN**



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.