




## PRODUCT DETAILS



## Dimensions



## Accessories



# JORY FLOOD S

**JORY FLOOD S 120° LED 150lm/830 1x5W,  
FIX, -**

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)


## Description

|                                      |  |
|--------------------------------------|--|
| <b>MOUNTING</b>                      | Wall mounted (WMD)   |
| <b>LIGHT SOURCE</b>                  | LED  |
| <b>OPTICAL SYSTEM</b>                | Lenses (LNS)   |
| <b>BEAM ANGLE</b>                    | 120°   |
| <b>LIGHT DISTRIBUTION</b>            | Direct   |
| <b>WIRING</b>                        | Electronic control gear FIX (ECG)                                |
| <b>MATERIALS</b>                     | Cover: transparent hardened glass<br>Housing: die-cast aluminium |
| <b>SURFACE FINISH</b>                | Housing: BRZ   |
| <b>VOLTAGE</b>                       | 220-240 V, 50-60 Hz  |
| <b>POWER FACTOR</b>                  | > 0,95   |
| <b>NET LUMEN OUTPUT (Ta=25°C)</b>    | 150 lm   |
| <b>LUMINOUS FLUX TOLERANCE</b>       | +/- 10 %   |
| <b>NUMBER OF LAMPS</b>               | 1  |
| <b>POWER CONSUMPTION</b>             | 5 W  |
| <b>SYSTEM EFFICACY</b>               | 30 lm/W  |
| <b>CORRELATED COLOUR TEMPERATURE</b> | 3000 K   |
| <b>COLOUR RENDERING INDEX</b>        | 80 Ra  |
| <b>EEC</b>                           | A++ / A+ / A   |
| <b>PROTECTION CLASS</b>              | I  |
| <b>THERMAL MANAGEMENT</b>            | Passive  |
| <b>SERVICE LIFETIME (Ta=25°C)</b>    | 50,000 hours / L70 / B50   |
| <b>AMBIENT OPERATING TEMPERATURE</b> | From -10 °C to +35 °C  |
| <b>IP PROTECTION DEGREE</b>          | IP67   |
| <b>MECHANICAL IMPACT RESISTANCE</b>  | IK08   |
| <b>DIMENSIONS (L x H)</b>            | 98 x 134 mm  |

## AREAS OF APPLICATION STREET AND URBAN



## LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.