

# Kombic 100 Downlight

## KOMBIC 100 Downlight



### DESCRIPTION:

KOMBIC 100 recessed downlight of 1500 or 2500 lm from Lamp brand. Die-cast aluminium dissipater. Models with opal or optical diffuser for greater visual comfort (reaching UGR <17 in some models) COB LED of 2700 K, 3000 K or 4000 K, with CRI of 80 or 90. On / Off or Dali with the possibility of control via bluetooth LE. With IP40 degree of protection. Isolation class I. Photobiological safety group 0.


### Available finishes:

- Opal model: Bright, metalized matt or white interior reflector and white exterior finishing.
- Optic model: Black interior reflector and black or white exterior finishing, or interior reflector in metalized matt or white and white exterior finishing.

**Dimensions:** diameter 99 mm or square section 99x99 mm.

**Weight:** 392 g

**INSTALLATION:** Recessed



### KOMBIC 100 DOWNLIGHT OPAL

Family	Installation	Lm LED	IP	Optic	CRI	K	Gear	Reflector Finishes	Ext. Finishes
K11	RD Round	15 1500lm	40 IP 40	OP Opal	9 90	27 2700 K	N ON/OFF D DALI	R Bright M Metalized Matt W White	W White O2
	SQ Square	20 2000lm				30 3000 K 40 4000 K			
		20 2000lm	40 IP 40	OP Opal	8 80	30 3000 K			
		25 2500lm				40 4000 K			

Code configurator:

### KOMBIC 100 DOWNLIGHT OPTIC

Family	Installation	Lm LED	IP	Optic	CRI	K	Gear	Reflector Finishes	Ext. Finishes
K11	RD Round	15 1500lm	40 IP 40	WF WFL 50°	9 90	27 2700 K	N ON/OFF D DALI	B Black M Metalized Matt W White	B Black O2 W White O2
	SQ Square	20 2000lm				30 3000 K 40 4000 K			
		20 2000lm	40 IP 40	WF WFL 50°	8 80	30 3000 K			
		25 2500lm				40 4000 K			

Code configurator:

## LIGHT OUTPUT AND POWER

### KOMBIC 100 DOWNLIGHT OPAL

	K	CRI	1500lm		2000lm		2500lm	
			W	lm Output	W	lm Output	W	lm Output
BR	2700	90	13	1191	19	1598	19	-
		80	-	-	13	-	19	-
	3000	90	13	1230	19	1648	19	-
		80	-	-	13	1460	19	1959
	4000	90	13	1336	19	1892	19	-
		80	-	-	13	1547	19	2075
MA	2700	90	13	1135	19	1523	19	-
		80	-	-	13	-	19	-
	3000	90	13	1172	19	1571	19	-
		80	-	-	13	1392	19	1867
	4000	90	13	1273	19	1708	19	-
		80	-	-	13	1474	19	1978
WH	2700	90	13	1186	19	1591	19	-
		80	-	-	13	-	19	-
	3000	90	13	1125	19	1642	19	-
		80	-	-	13	1454	19	1951
	4000	90	13	1330	19	1785	19	-
		80	-	-	13	1541	19	2067

### KOMBIC 100 DOWNLIGHT OPTIC

	K	CRI	1500lm		2000lm		2500lm	
			W	lm Output	W	lm Output	W	lm Output
BK	2700	90	13	983	19	1312	-	-
		80	-	-	-	-	-	-
	3000	90	13	1015	19	1354	-	-
		80	-	-	14	1205	20	1609
	4000	90	13	1102	14	1472	-	-
		80	-	-	14	1277	20	1704
MA	2700	90	13	1030	19	1380	-	-
		80	-	-	-	-	-	-
	3000	90	13	1068	19	1424	-	-
		80	-	-	14	1268	20	1692
	4000	90	13	1160	14	1548	-	-
		80	-	-	14	1343	20	1792
WH	2700	90	13	1040	19	1387	-	-
		80	-	-	-	-	-	-
	3000	90	13	1074	19	1432	-	-
		80	-	-	14	1275	20	1701
	4000	90	13	1166	14	1556	-	-
		80	-	-	14	1351	20	1802

# Kombic 100 Downlight

## FINISHES:

- B:** Black 02: ● RAL 9011 BLACK MATE
- W:** White 02: ○ RAL 9010 WHITE MATE

## TECHNICAL SPECIFICATIONS:




## QUALITY CERTIFICATES:




## PHOTOMETRIC DATA :


### Opal



### WFL 50°



### Opal



### WFL 50°

