K11RD2040WF9TWDMW

KOMBIC 100 RD 2000 IP40 TW WFL DA MA/WH

Description:

Round recessed downlight model KOMBIC 100 RD 2000 IP40 TW WFL DA MA/WH, LAMP brand. Reflector made of polycarbonate. Matte metallic interior reflector and frame in white finish, injected aluminium dissipator. Model for LED COB, with dynamic white color temperature and control gear included IP40 protection rating. Optic Wide Flood to achieve a controlled light distribution and low glare level, less than UGR 17. Insulation class II.

Finish: Shiny white RAL 9010

Weight: 550 g

IEE : A

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.050 lm	**ºK :**	2700-5000
Plum:	20.7W	**CRI :**	90
Efficacy:	50,7 lm/w	**MacAdam:**	3
Type:	BRIDGELUX	**Alimentación:**	220-240V 50/60Hz
LED Lifetime:	70.000 L80 B10	**Gear:**	Adjustable DALI
Power:	16W		

CUSTOM MADE OPTIONS:

K11RD2040WF9TWDMW **KOMBIC 100 RD 2000 IP40 TW WFL DA MA/WH**

PHOTOMETRIC DATA :

K21RD3040OP9TWDMW

η = 100%

Imax = 1093 cd/klm

UTE: 1,00A

CIE: 88 100 100 100 100

Melanopic Lux Ratio: 0.772