

Product datasheet
KOMBIC 200

 K31RD50400P840NRW **KOMBIC 200 RD 5000 IP44 NW OPAL BR/WH**


Description:

Round recessed downlight model KOMBIC 200 RD 5000 IP44 NW OPAL BR/WH, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model f or COB LED, with neutral white colour temperature and control gear included. IP44 protection rating. Insulation class II.

Finish: Shiny white RAL 9010

Weight: 1.536 g

IEE : A+

Installation: Recessed

Lamp:


Type: COB PHILIPS
LED Lifetime: 50.000 L70 B10
Power: 36W

°K : 4000
CRI : 80
MacAdam: 3

Electrical features:

Gear: Electronic
Plum: 39W

Power Supply: 220-240V 50/60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}	alpha = 53,6°	Beam spread diagram	Technical data
1	1,01	3916	2469			9241530 η = 100% I _{max} = 976 cd/klm UTE: 1,00B + 0,00T CIE: 80 98 100 100 100
2	2,02	979	617			
3	3,03	435	274			
4	4,04	245	154			

Light output: 4.016 lm **Efficacy:** 103 lm/w

Optical




Product code: ADRD250W
Description: KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code: DITRD240B
Description: DOMO 220/KOMBIC ACC. TRANSP GLASS BK.



Product code: DITRD240G
Description: DOMO 220/KOMBIC ACC. TRANSP GLASS GR.
DITRD240W DOMO 220/KOMBIC ACC. TRANSP GLASS WH.



Product code: RIRD240B
Description: DOMO 220/KOMBIC ACC. DECO RING BK.



Product code: RIRD240G
Description: DOMO 220/KOMBIC ACC. DECO RING GR.
RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.

