

KOMBIC 200

K31RD4040OP830NRW **KOMBIC 200 RD 4000 IP44 WW OPAL BR/WH**



Description:


Round recessed downlight model KOMBIC 200 RD 4000 IP44 WW OPAL BR/WH, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model f or MID-POWER LED, with warm white colour temperature and control gear included. IP44 protection rating. Insulation class II. Photobiological safety group 0.

Finish: Shiny white RAL 9010

Weight: 976 g

IEE : A+

Installation: Recessed



Lamp:

Type:	MID POWER TRIDONIC	°K :	3000
LED Lifetime:	50.000 L80 B10	CRI :	80
Power:	24W	MacAdam:	3

Electrical features:

Gear:	Electronic	Power Supply:	220-240V 50/60Hz
Plum:	25.4W		

Technical features:



Quality certificates:



Photometrical data:


H (m)	D (m)	E _{max}	E _{med}	Diagram 1	Diagram 2	Diagram 3
1	1,03	2647	1631			<p>9241370 η = 100% I_{max} = 947 cd/klm UTE: 1,00B + 0,00T CIE: 78 98 100 100 100</p>
2	2,07	662	408			
3	3,10	294	181			
4	4,13	165	102			

Light output: 2.800 lm **Efficacy:** 110,2 lm/w

Optical



Product code: ADRD250W
Description: KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code: DITRRD240B
Description: DOMO 220/KOMBIC ACC.TRANSF GLASS BK.



Product code: DITRRD240G
Description: DOMO 220/KOMBIC ACC.TRANSF GLASS GR.
DITRRD240W DOMO 220/KOMBIC ACC.TRANSF GLASS WH.



Product code: RIRD240B
Description: DOMO 220/KOMBIC ACC. DECO RING BK.



Product code: RIRD240G
Description: DOMO 220/KOMBIC ACC. DECO RING GR.
RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.