

Product datasheet
KOMBIC

 9241380 **KOMBIC BRIGHT 4000 NW**


Description:

Round recessed downlight model KOMBIC BRIGHT 4000 NW, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and bright metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for MID-POWER LED, with neutral white colour temperature and control gear included. IP44 protection rating. Insulation class II.

Finish: Shiny white

Weight: 976 g

IEE : A+

Installation: Recessed

Lamp:
Type: MID POWER TRIDONIC

LED Lifetime: 50.000 L80 B10

Power: 24W

°K : 4000


CRI : 80

MacAdam: 3

Electrical features:
Gear: Electronic

Plum: 25.4W

Power Supply: 220-240V 50-60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}	alpha = 54,6°	Beam spread diagram	Technical data
1	1,03	2783	1714			9241380 η = 100% I _{max} = 947 cd/klm UTE: 1,00B + 0,00T CIE: 78 98 100 100 100
2	2,07	696	429			
3	3,10	309	190			
4	4,13	174	107			

Light output: 2.944 lm **Efficacy:** 115,9 lm/w

Tel. +34937366800

Fax +34937861551

Web www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es.

Complies with the Directive 2010/30/UE

03-11-2018

Pág. 1 / 1