

Product datasheet
KOMBIC 200

 K31RD4040OP830NMW **KOMBIC 200 RD 4000 IP44 WW OPAL MA/WH**


Description:

Round recessed downlight model KOMBIC 200 RD 4000 IP44 WW OPAL MA/WH, LAMP brand. Interior diffuser made of opal methacrylate specially for LED and matt metallic reflector, injection aluminium dissipator and TOR KIT type easy-fit fastening system. Model for COB LED, with warm white colour temperature and control gear included. IP44 protection rating. Insulation class II. Photobiological safety group 0.

Finish: Shiny white RAL 9010

Weight: 976 g

IEE : A+

Installation: Recessed

Lamp:
Type: COB TRIDONIC

LED Lifetime: 50.000 L80 B10

Power: 24W

°K : 3000


CRI : 80

MacAdam: 3

Electrical features:
Gear: Electronic

Plum: 25.4W

Power Supply: 220-240V 50/60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}	alpha = 77,7°	180°	90°	90°	0°	9241371 η = 100% I _{max} = 641 cd/klm UTE: 1,00B + 0,00T CIE: 71 95 99 100 100
1	1,61	1720	871						
2	3,22	430	218						
3	4,84	191	97						
4	6,45	108	54						

Light output: 2.688 lm **Efficacy:** 105,8 lm/w

Optical




Product code: ADRD250W
Description: KOMBIC ACC. Ø250 ADAPTER RING WH.



Product code: DITRD240B
Description: DOMO 220/KOMBIC ACC. TRANSP GLASS BK.



Product code: DITRD240G
Description: DOMO 220/KOMBIC ACC. TRANSP GLASS GR.
DITRD240W DOMO 220/KOMBIC ACC. TRANSP GLASS WH.



Product code: RIRD240B
Description: DOMO 220/KOMBIC ACC. DECO RING BK.



Product code: RIRD240G
Description: DOMO 220/KOMBIC ACC. DECO RING GR.
RIRD240W DOMO 220/KOMBIC ACC. DECO RING WH.

