

Product datasheet

KOMBIC SURFACE

10141000 KOMBIC SUR 2000 WW WH.



Description:

Suspended or ceiling mounting downlight model KOMBIC SUR 2000 WW WH., LAMP brand. Made of white colour injected polycarbonate with shiny metallized reflector and interior diffuser made of opal methacrylate. Passive dissipation for a proper thermal management. Model for COB LED with warm white colour temperature and control gear included. Insulation class II.

Finish: Matte white

Weight: 1.618 g

IEE : A+

Installation: Surface

Lamp:
Type: COB CITIZEN

LED Lifetime: 50.000 L80 B10

Power: 18W

°K : 3000


CRI : 80

MacAdam: 3

Electrical features:
Gear: Electronic



Plum: 20W

Power Supply: 220-240V 50-60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}
1	0,91	1915	1289
2	1,82	479	322
3	2,73	213	143
4	3,64	120	81



10141000 $\eta = 100\%$ $I_{max} = 1025 \text{ cd/klm}$ $UTE: 1,00B + 0,00T$ $CIE: 80 \ 98 \ 100 \ 100 \ 100$

Light output: 1.741 lm **Efficacy:** 87,1 lm/w