

Product datasheet

KOMBIC 200 SURFACE

 K31SF4020OP840NRW **KOMBIC 200 SF 4000 IP20 NW OPAL BR/WH**


Description:

Suspended or ceiling mounting Downlight model KOMBIC 200 SF 4000 IP20 NW OPAL BR/WH, LAMP brand. Made of white colour injected polycarbonate with shiny metallized reflector and interior diffuser made of opal methacrylate. Passive dissipation for a proper thermal management. Model for MID POWER LED with neutral white temperature and control gear included. Insulation class II. Photobiological safety group 0.

Finish: Matte white RAL 9010

Weight: 2.262 g

IEE : A+

Installation: Surface

Lamp:
Type: MID POWER TRIDONIC

LED Lifetime: 50.000 L80 B10

Power: 24W

°K : 4000

CRI : 80

MacAdam: 3

Electrical features:
Gear: Electronic

Plum: 25.8W

Power Supply: 220-240V 50/60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}	Diagram 1	Diagram 2	Diagram 3
1	1,03	2783	1714			10141050 $\eta = 100\%$ $I_{max} = 947 \text{ cd/klm}$ UTE: 1,00B + 0,00T CIE: 78 98 100 100 100
2	2,07	696	429			
3	3,10	309	190			
4	4,13	174	107			

Light output: 2.944 lm **Efficacy:** 114,1 lm/w

Assembly



Product code: K3SUCOW
Description: KOMBIC 200 SF ACC. COVER


Suspension



Product code: SUCARG0100G
Description: ACC. ELECMEC RIGID SUSP 100MM GR.
SUCARG0250G ACC. ELECMEC RIGID SUSP 250MM GR.
SUCARG0500G ACC. ELECMEC RIGID SUSP 500MM GR.
SUCARG1000G ACC. ELECMEC RIGID SUSP 1000MM GR.



Product code: SUCARG0100W
Description: ACC. ELECMEC RIGID SUSP 100MM WH.
SUCARG0250W ACC. ELECMEC RIGID SUSP 250MM WH.
SUCARG0500W ACC. ELECMEC RIGID SUSP 500MM WH.
SUCARG1000W ACC. ELECMEC RIGID SUSP 1000MM WH.



Product code: SUEM2W3000NG
Description: ACC. DB ELECMEC SUSP GR.



Product code: SUEM2W3000NW
Description: ACC. DB ELECMEC SUSP WH.