




Dimensions	
Product dimensions (mm)	50 x 110 x 110
Net weight (g)	107
Gross weight (Kg)	0,18

Scheme	
Scheme	



Product	
Real power (W)	8
Real luminous flux (Lm)	237
Luminous efficiency (Lm/W)	29,6
Beam angle (°)	82
Life time (h)	50000
IP	54
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anthracite
Energy efficiency class	A

Control gear	
Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,9

Light source	
Light source included	Yes
Light source	Led
Nominal power (W)	7,2
Nominal luminous flux (Lm)	273
Colour temperature (K)	4000
CRI	80

Photometry	
------------	--

Outdoor sconce from the TROLL family Kubik.

DESCRIPTION

Outdoor sconce from the TROLL family Kubik setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as accent lighting to create light effects on façades or lighting passing areas. Designed for wall surface mounted. Luminaire body built in die-cast aluminium finished in anthracite. Luminaire is IP54. Luminaire built-in an independent lens system for each led with an angle beam of 105°. Luminaire sets a 8 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 237 Lm, with an efficiency of 29,6 Lm/W and a total consumption of 8 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.1611.0005.22
Product type	OUT
Category	Surface
Family	Kubik
Subfamily	Kubik
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in an independent lens system for each led.
Installation instructions	Luminaire designed for wall surface mounted.
Pictograms	 

Photometry

