





PRODUCT DETAILS



Dimensions



Accessories



LAMBDA LED D-I

LAMBDA LED D-I L MICROPRISMA LED
7500lm/830 1x59W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
LIGHT DISTRIBUTION	Direct-indirect
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: PMMA Housing: sheet steel Rope suspension (suspended version)
SURFACE FINISH	Housing: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	7500 lm
POWER CONSUMPTION	59 W
SYSTEM EFFICACY	127 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L90 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1560 x 120 x 60 mm
WEIGHT	6,3 kg


AREAS OF APPLICATION [EDUCATION](#)

[HEALTH AND CARE](#)

[OFFICE](#)



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.