

LAMP TUB 60 SUSPENDED TRACK

L61ST084LOOC930DB



LTUB60 SUT 840 1500 WW COMF DA BK

Description:

Lamp tub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for MID-POWER LED, with colour temperature 3000K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011**Dimensions:** 847 x 67 x 80 mm**Weight:** 2.110 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	698 lm	°K :	3000
Plum:	10W	CRI :	90
Efficacy:	69,8 lm/w	R9 :	64
UGR:	19	MacAdam:	3
Type:	MID POWER	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10	Gear:	Adjustable DALI
Power:	8.5W		

**CUSTOM MADE OPTIONS:**

LAMPTUB 60 SUSPENDED TRACK



L61ST084LOOC930DB

LTUB60 SUT 840 1500 WW COMF DA BK

PHOTOMETRIC DATA :

