

# LAMPTUB 60 SUSPENDED TRACK


L61ST084LOIO930NB



LTUB60 SUT 840 1500 WW D/I OPAL BK

**Description:**

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



**Finish:** Matte black RAL 9011

**Dimensions:** 847 x 67 x 80 mm

**Weight:** 2.110 g

**Installation:** 3-Circuit track

**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.386 lm	<b>°K :</b>	3000
<b>Plum:</b>	20W	<b>CRI :</b>	90
<b>Efficacy:</b>	69,3 lm/w	<b>R9 :</b>	64
<b>Type:</b>	MID POWER	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	72.000 L80 B10	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	17W	<b>Gear:</b>	Electronic



**CUSTOM MADE OPTIONS:**



# LAMPTUB 60 SUSPENDED TRACK

L61ST084LOIO930NB

LTUB60 SUT 840 1500 WW D/I OPAL BK

**PHOTOMETRIC DATA :**

L61ST084LOIO930NB  
 $\eta = 100\%$   
 $I_{max} = 213 \text{ cd/klm}$   
 UTE: 0,55E + 0,46T  
 CIE: 50 81 97 54 100

