



PRODUCT FAMILY DATASHEET

LED SUPERSTAR DOWNLIGHT

Spotlights and downlights



AREAS OF APPLICATION

- Corridors, entrances, foyers, stairwells, elevators
- Secondary rooms

PRODUCT BENEFITS

- Direct connection to AC power supply thanks to integrated control gear
- Plug and Play due to EU Plug
- Energy-saving alternative to luminaires that use halogen lamps
- Bright, robust and durable
- Uniform room illumination
- Long lifetime thanks to LED technology
- Mercury-free technology

PRODUCT FEATURES

- Available with color temperature: 3,000 K, 4,000 K, 5,000 K
- Initial color consistency: < 5 SDCM
- Color rendering index R_a : ≥ 80
- Beam angle: 100°
- Type of protection: IP20




- Power factor: > 0.9

TECHNICAL DATA

Product description	Electrical data			Photometrical data		Dimensions & weight			Colors & materials	Temperatures & operating conditions	Lifespan
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Diameter	Height	Product weight	Product color	Ambient temperature range	Number of switching cycles
LED SST D/L 8.00 W 3000 K KIT	8.00 W	240 V	50/60 Hz	3000 K	800 lm	115.0 mm	60.0 mm	231.00 g	White	-20...40 °C	100000
LED SST D/L 8.00 W 4000 K KIT	8.00 W	240 V	50/60 Hz	4000 K	850 lm	115.0 mm	60.0 mm	231.00 g	White	-20...40 °C	100000
LED SST D/L 8.00 W 5000 K KIT	8.00 W	240 V	50/60 Hz	5000 K	900 lm	115.0 mm	60.0 mm	231.00 g	White	-20...40 °C	100000

Product description	Capabilities		Certificates & standards	
	Dimmable	Type of connection	Protection class	Type of protection
LED SST D/L 8.00 W 3000 K KIT	Yes	Plug, EU	II	IP44
LED SST D/L 8.00 W 4000 K KIT	Yes	Plug, EU	II	IP44
LED SST D/L 8.00 W 5000 K KIT	Yes	Plug, EU	II	IP44



LED SST D/L 8.00 W 3000 K KIT, LED
 SST D/L 8.00 W 4000 K KIT, LED SST
 D/L 8.00 W 5000 K KIT

EQUIPMENT / ACCESSORIES

– Satin chrome trim available as accessories

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075014916	Shipping carton box 12	263 mm x 263 mm x 250 mm	3330.00 g	17.29 dm ³
4058075014978	Shipping carton box 24	580 mm x 380 mm x 260 mm	6710.00 g	57.30 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075014930	Shipping carton box 12	263 mm x 263 mm x 250 mm	3330.00 g	17.29 dm ³
4058075014992	Shipping carton box 24	580 mm x 380 mm x 260 mm	6710.00 g	57.30 dm ³
4058075014954	Shipping carton box 12	263 mm x 263 mm x 250 mm	3330.00 g	17.29 dm ³
4058075015012	Shipping carton box 24	580 mm x 380 mm x 260 mm	6710.00 g	57.30 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.