

PRODUCT DATASHEET

LED VALUE PANEL 32 W 3000 K 4000 6500

LED VALUE TRI-COLOUR PANEL | LED panel luminaires with slide switch for adjusting one of selectable light colors



AREAS OF APPLICATION

- Retail
- Hospitals
- Office areas

PRODUCT BENEFITS

- Edge-lit with LCD backlight technology
- Low flicker light thanks to special electronic control gear
- Elegant design thanks to slim seamless white frame made of aluminum

PRODUCT FEATURES

- Aluminum housing, PMMA diffuser
- High luminous efficacy: up to 100 lm/W
- Three light colors selectable via slide switch
- RCM marked, CB test certificate
- Color rendering index R_a : > 80
- Power factor: > 0.9
- Lifetime: up to 30,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	32.00 W
Nominal voltage	220...240 V
Power factor λ	0.90

Photometrical data

Color temperature	3000/4000/6500 K
Color rendering index Ra	≥ 80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	3200 lm
Luminous efficacy	100 lm/W
Standard deviation of color matching	≤ 6 sdcn

Light technical data

Beam angle	120 °
------------	-------

Dimensions & weight

Length	1195 mm
Width	295.0 mm
Height	9.0 mm
Product weight	2750.00 g

Colors & materials

Housing color	White
Product color	White
Body material	Aluminum

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities

Dimmable	No
LED module replaceable	Not replaceable

Certificates & standards

Type of protection	IP20
Protection class	II

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075277090	Folding carton box 1	1232 mm x 37 mm x 364 mm	3289.00 g	16.59 dm ³
4058075277106	Shipping carton box 5	1247 mm x 205 mm x 390 mm	18034.00 g	99.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.