

Product datasheet
MUN LIGHT

 ML1480SF40840NW **MUN LIGHT SUR Ø480 4000 NW WH.**


Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480 4000 NW WH., LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with neutral white color temperature and control gear included. IP20 protection rating. Insulation class I.

Finish: Texturised matte white RAL 9016

Weight: 6.800 g

IEE : A+

Installation: Surface

Lamp:
Type: MID POWER OSRAM

LED Lifetime: 50.000 L80 B10

Power: 59W

°K : 4000

CRI : 80

MacAdam: <3

Electrical features:
Gear: Electronic

Plum: 61.9W

Power Supply: 220-240V 50/60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}	alpha = 114,4°	Beam angle diagram	Technical data
1	3,10	1573	453			10540030 η = 100% I _{max} = 344 cd/klm UTE: 1,00E + 0,00T CIE: 47 79 96 100 100
2	6,21	393	113			
3	9,31	175	50			
4	12,41	98	28			

Light output: 4.576 lm **Efficacy:** 73,9 lm/w

Tel. +34937366800

Fax +34937861551

Web www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es.

Complies with the Directive 2010/30/UE

18-08-2020

Pág. 1 / 1