

Product datasheet
MUN LIGHT

 ML1300SF30830NW **MUN LIGHT SUR Ø300 3000 WW WH.**


Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø300 3000 WW WH., LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with warm white color temperature and control gear include d. IP20 protection rating. Insulation class I.

Finish: Texturised matte white RAL 9016

Weight: 2.900 g

IEE : A+

Installation: Surface

Lamp:
Type: MID POWER OSRAM

LED Lifetime: 50.000 L80 B10

Power: 22W

°K : 3000

CRI : 80

MacAdam: <3

Electrical features:
Gear: Electronic

Plum: 26.2W

Power Supply: 220-240V 50/60Hz

Technical features:

Quality certificates:

Photometrical data:

H (m)	D (m)	E _{max}	E _{med}	Diagram	Beam Angle	Beam Diameter
1	3,07	558	163		113,9°	3,07 m
2	6,15	140	41			
3	9,22	62	18			
4	12,30	35	10			

Light output: 1.613 lm **Efficacy:** 61,6 lm/w

Tel. +34937366800

Fax +34937861551

Web www.lamp.es

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es.

Complies with the Directive 2010/30/UE

18-08-2020

Pág. 1 / 1