








Nightpath bollard

With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, light head IP65 $\blacklozenge\blacktriangle\blacktriangle$, IK08
corrosion-resistant die cast aluminium housing AlSi12,
extruded aluminium post,
cast aluminium base plate,
polyester powder coated,
extreme wide beam optical system,
tempered prismatic safety glass,
all exterior steel parts are stainless steel,
silicone gasket, closure by 4 stainless steel screws,
integral driver



Nightpath bollard, height 600 mm

Part number*	Colour	Light source	Luminous flux	Beam angle γ (FWHM)
8 304 646 009	black	5 x LED 2.5 W	550 lm	88°
8 304 666 009	white	warm white (3000 K)		
8 304 656 009	silver grey			

*These luminaires are also available with neutral white LEDs (4000 K) upon request.

Nightpath bollard, height 1000 mm

Part number*	Colour	Light source	Luminous flux	Beam angle γ (FWHM)
8 304 146 009	black	5 x LED 2.5 W	550 lm	88°
8 304 166 009	white	warm white (3000 K)		
8 304 156 009	silver grey			

*These luminaires are also available with neutral white LEDs (4000 K) upon request.


Nightpath bollard with door and connection box

Part number	Description
... .. 1.	Luminaire with door and connection box

Accessories Nightpath bollard

Part number	Description
128 0 346 000	Buried extension piece, steel, hot dip galvanised

Part number	Description
123 0 270 000	Polycarbonate cover, for protection against vandalism, for flush mounting in luminaire housing (IK10)



LED (see page 185)

Luminaires available in 2700 K and other colour temperatures on request

