



## MÜNCHEN LED m600

2630lm, PC Tropol® (fracture proof), 840/4000K, medium beam

Article No: 455 280 34 84 - MC7



illustration may differ



XARA® (optional)

medium beam

### DIMENSIONS

L	B	H	a	b	max. weight
782 mm	191 mm	80 mm	493 mm	-	3.5 kg

### DESCRIPTION

Ceiling and recessed polymer luminaire with LED lamps. Flat and weather-proof polymer luminaire housing. Thermally separated lamp chamber and transformer chamber. Short sealing system consisting of age resistant, form retaining silicone/synthetic rubber. Lamp diffuser with internal aluminium reflector (MIRO-SILVER®). Built-in transformer. Ready for connection with two access covers (360 mm), four M20 cable entries on face side and through wiring. Mounting with split washers for easy assembly. Captive end caps.

created on: 2018-10-16 (ext.) Subject to technical changes without prior notice

# MÜNCHEN LED m600

2630lm, PC Tropol® (fracture proof), 840/4000K, medium beam

Article No: 455 280 34 84 - MC7

## CHARACTERISTICS

<b>Version</b>	m600	<b>Lamp power</b>	1 x 16 W
<b>Lamp</b>	LED	<b>System power</b>	19 W
<b>Lamp service life</b>	L80 B10 > 60.000 h at +40°C	<b>Colour temperature</b>	White, 840/4000 K, Ra > 80
<b>Extreme-temperature</b>	-25°C to +40°C	<b>Luminous flux lamp</b>	2630 lm
<b>Number of lamps</b>	1-lamp	<b>Protection class</b>	II
<b>Cover material</b>	Plastic	<b>IP-rating</b>	IP65
<b>Colour housing</b>	White	<b>Type of gear</b>	LED operating device current-controlled, Not dimmable, 220 V - 240 V AC/DC
<b>Cover</b>	PC Tropol® (fracture proof)	<b>Through-wiring</b>	4 x 1,5 mm <sup>2</sup>
<b>Light distribution</b>	medium beam	<b>Impact strength</b>	IK08
<b>Manufacturer warranty</b>	5 years	<b>Installation type</b>	recessed mounted, Surface mounting, recessed mounting, ceiling mounting, single mounting, row mounting
<b>ENEC / VDE</b>	YESYES		
<b>EL (Emergency Lighting)</b>	optional		

## DIAGRAMS

